

IP / Professional NVRs

# SF-NVR6108-4KE-8P

## Network Video Recorder for IP Cameras

### 4K NVR 6 VS2 Series

Network recorders with great flexibility of use, even with ultra-high resolution 4K cameras or highly efficient H.265+ encoding. Monitoring up to 1 Ch@4K or 4 Ch@1080p with auto-adaptive mode that achieves simultaneous display of a large number of cameras without exhausting graphic resources. Its 4K HDMI output allows maximum use of UHD monitors. Versions with integrated PoE power supply and auto-add-on mode for simplified and centralised installation.

- 8Channels IP video
- Decoding capacity 8MP
- Compression technology H.265+/H.265
- Total bandwidth 80 Mbps
- PoE (Power Over Ethernet) technology
- 4K HDMI and VGA Output
- Space for 1 HDD



## Technical Specification

<b>Entrada de vídeo IP</b>	8-ch
<b>HDMI Output</b>	1-ch, 4K (3840 × 2160)/30Hz, 1920 × 1080p/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz; HDMI/VGA simultaneous output
<b>VGA Output</b>	1-ch, 1920 × 1080p/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz ;HDMI/VGA simultaneous output
<b>Incoming Bandwidth</b>	80 Mbps
<b>Outgoing Bandwidth</b>	80 Mbps
<b>Salida de audio</b>	1-ch, RCA (Linear, 1 K $\Omega$ )
<b>Two-Way Audio</b>	1-ch, RCA (2.0 Vp-p, 1 k $\Omega$ )
<b>Formato de decodificación</b>	H.265+,H.265,H.264+,H.264
<b>Decodificación</b>	4-ch@1080p
<b>Reproducción síncrona</b>	8-ch
<b>Resolución de grabación</b>	8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF
<b>Protocolo de red</b>	TCP/IP, DHCP, Safire Connect, DNS, DDNS, NTP, SADP, SMTP, NFS, iSCSI, UPnP™, HTTPS
<b>Interfaz de red</b>	1, RJ-45 10/100 Mbps self-adaptive Ethernet interface
<b>Interfaz</b>	8-ch
<b>alimentación</b>	≤ 75W
<b>RAID Type</b>	No
<b>SATA</b>	1 SATA interface
<b>Capacidad</b>	Up to 8TB capacity for each disk
<b>Interfaz USB</b>	2 × USB 2.0
<b>Fuente de alimentación</b>	48 VDC, 1.8 A
<b>Consumo</b>	≤ 10 W (without enabling PoE)
<b>Temperatura de trabajo</b>	-10 to +55° C (+14 to +131° F)
<b>Condiciones de Humedad</b>	10 to 90 %
<b>Chassis</b>	1U chassis
<b>Dimensión (W × D × H)</b>	320 × 240 × 48 mm (12.4" × 9.4" × 1.9")   ≤ 1 kg (2.2 lb)