

Video-intercoms / Outdoors Station

SF-VIMOD-CAM-IP

Outdoor station

Modular Outdoor Station

The line up of modular video intercoms is aimed at all types of environments, villas or apartments. Aesthetic and compact design, suitable for all types of installations thanks to its IP or 2-wire communication modes. 2MP camera with perfect visualization of the entire environment thanks to its 180° image angle, it also stands out for its night image. Second door activation function for users who need it. With different functionalities that every type client wants such as two-way audio, remote access from the app and remote door unlocking. It has a possible add-ons of different modules to make it more complete such as unlocking by cards or password or calling the different apartments.

- Modular Videointercom IP
- Standard PoE
- Bidirectional Audio
- 2 relay for doors
- 2 Mpx Camera with Viewing angle 180°
- Mobile App
- Outdoor Installation



Technical Specification

Supplement light	IR supplement
Lens	1
FOV	Horizontal: 180° Vertical: 96°
Pixel	Main stream : 1920 × 1080 Sub stream : 720 × 480
Audio quality	Noise suppression and echo cancellation
Sub door station capacity	16
Communication protocol	TCP/IP, RSTP
Wired network	10/100 Mbps self-adaptive Ethernet
Network interface	1
Exit button	2
Lock control	2
Door contact input	2
Power interface	1
Button	1
Installation	Flush Mounting Surface Mounting
Weight	Without package: 345 g
Protective level	IP65
Power supply method	12 VDC/PoE (IEEE 802.3af)
Working temperature	-40° C to +55° C(-40° F to 131° F)
Working humidity	10% to 95%
Dimensions	Door station:98 mm × 99.8 mm × 43.9 mm (3.86" ×3.93" × 1.73") Cover:134 × 124 × 4 mm(5.28" × 4.88" ×0.16") Gang box:134 × 135 × 56 mm(5.28" × 5.31" ×2.20")
Application environment	Outdoor
Power consumption	≤ 10 W
Platform	Safire Connect & Safire Control Center