

CCTV Analógico / HD 4n1 / Cameras

## SF-T020-2B1-DL

### SF-T020-2B1

#### B1 Range: Budget Friendly and Basic Functions

With models ranging from 2MP to 5MP, the B1 range provides an analogue solution at a very competitive price. Models are available with NightColor functionality, offering 24-hour colour viewing. They come with Smart IR (white supplementary light) which will allow colour viewing in case the light gets low enough. With a very affordable price, this range offers simple but very efficient features for the most basic installations, such as 2D DNR technology for noise reduction or DWDR to improve image quality.

- Turret camera 4 in 1 Range B1
- 2 Mpx (1920x1080) , 1/3" CMOS
- Lens 2.8mm | IR range 30 m
- DWDR, HLC, BLC, AGC
- Weatherproof IP67



## Technical Specification

Camera	
Image Sensor	1 / 3"CMOS
Resolution	2MP
Image Size	1920 x 1080
Video Output	AHD / TVI /CVI/CVBS
Image System	PAL / NTSC
Electronic Shutter	Auto; 1 / 50s ~ 1 / 100000s ( PAL ); 1 / 60s ~ 1 / 100000s ( NTSC )
IR Distance	20 ~30 m
Frame Rate	30fps(60Hz); 25fps (50Hz)
Min. Illumination	0 lux (IR ON)
Lens	2.8mm
Lens Mount	M12
S / N Ratio	≥52dB ( AGC OFF )
Ingress Protection	IP 67
Functions	
Function Control	OSD ( COC Control )
Day & Night	ICR
Digital WDR	Yes
Digital DNR	Yes (2D/3D DNR)
AGC	Yes
Auto White Balance	Yes
BLC	Yes
Front Light Compensation	Yes
Defog	No
HLC	No
Sharpness	Yes
Mirror	No
Smart IR	Yes
Image Setting	Yes
Defect Correction	Auto

<b>Language</b>	Chinese and English
<b>Angle Adjustment</b>	Pan: 0°~360°; Tilt: 0°~75°; Rotation: 0°~360°
<b>Others</b>	
<b>Power Supply</b>	DC12V ( ± 10% )
<b>Power Consumption</b>	IR OFF : < 1W; IR ON : < 3W
<b>Working Environment</b>	- 30 °C ~ 50 °C, 10 % ~ 90 % (relative humidity)
<b>Dimensions ( mm )</b>	□ 94.6 x 82.8
<b>Weight ( net )</b>	Approx. 0.39KG