

IP CCTV / Professional IP cameras / Hikvision / Turret cameras

DS-2CD1363G2-LIU(2.8mm)

HIKVISION



Features

- Hikvision
- Value Range
- Turret IP Camera
- 1/2.4" Progressive Scan CMOS
- 6 Megapixel (3200x1800)
- 2.8 mm Lens
- 0 Lux
- Hybrid light: IR and White Light range 30 m
- Compression H.265+ / H.265 / H.264+ / H.264
- Weatherproof IP67
- Motion detection 2.0
- WDR (120 dB)
- 3D DNR
- Integrated microphone
- WEB, CMS, Smartphone and NVR interface
- ONVIF Compatible
- PoE (IEEE802.3af)

Specifications

Brand	HIKVISION
Range	Value
Image sensor	1/2.4" Progressive Scan CMOS
Maximum resolution	6 Megapixel (3200x1800)
Main Stream rate	20 fps (3200x1800, 2688x1520, 1920x1080, 1280x720) [%VAR%]
Extra Stream rate	20 fps (1280x720, 640x480, 640x360)
Compression	H.265+ / H.264+ / H.265 / H.264
Bitrate	32 Kbps ~ 16 Mbps
Lens	2.8 mm
Viewing Angle (FOV)	H: 105°, V: 55°, D: 127°
Range performance	76 m (D), 30 m (O), 15 m (R), 7 m (I)
Electronic Shutter	1/3~1/100.000 s
Minimum illumination	Colour: 0.005 Lux @(F1.6, AGC ON) 0 Lux with IR range 30 m
Supplementary lighting	Hybrid light: IR Range 30 m White light range 30 m
Day/Night	Removable mechanical ICR filter
Image improvements	WDR (120 dB), BLC, HLC, 3D-DNR, AGC, AWB, ROI, Mirror function, Privacy masking
Motion Detection	Motion detection 2.0 with human and vehicle classification applied in motion detection.
Network interface	Ethernet 10 / 100 BaseT
Remote access	Web Browser, Hik-Connect Smartphone App, PC Software iVMS-4200 and Hik-Central
Interoperability	ONVIF, ISAPI
Power	DC 12 V / 410 mA / 5 W max. / IEEE802.3af PoE
Degree of protection	Weatherproof IP67
Material	Metal and plastic
Temp. operation	-30° C ~ +60° C

Dimensions Ø 110 x 89.2 mm (Al)

Base dimensions Ø base 110 mm / Ø between bolts 85 mm / 3 bolts

Weight 340 g
