

## DS-7100NI-K1/W/M(C) Series Wi-Fi NVR

### Key Feature

- H.265+/H.265/H.264+/H.264 video compression
- Up to 50 Mbps incoming bandwidth, and 40 Mbps outgoing bandwidth
- Up to 4/8-ch network camera inputs
- Up to 4-ch@4 MP decoding capability
- HDMI and VGA simultaneous output
- Easy and stable Wi-Fi connection



### Compression and Recording

- H.265+ compression effectively reduces the storage space by up to 75%
- Full channel recording at up to 4 MP resolution

### Storage and Playback

- 4-ch@4 MP (12 fps) or 4-ch@1080p (25 fps) playback resolution
- 1 SATA interface (up to 6 TB capacity per HDD)

### Smart Function

- Supports line crossing and intrusion detection

### Network & Ethernet Access

- Dual external antenna design offers more powerful and stable signal
- 1 self-adaptive 10/100 Mbps Ethernet interface
- Hik-Connect for easy network management




## Specification

Model	DS-7104NI-K1/W/M(C)	DS-7108NI-K1/W/M(C)
<b>Video and Audio</b>		
IP video input	4-ch	8-ch
	Up to 4 MP resolution	
Incoming bandwidth	50 Mbps	
Outgoing bandwidth	40 Mbps	
HDMI output	1-ch, 1920 × 1080p/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz	
VGA output	1-ch, 1920 × 1080p/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz, HDMI/VGA simultaneous output	
Audio output	1-ch, RCA (linear, 1 KΩ)	
Audio decoding format	G.711ulaw,G.722,G.726,MP2L2	
Two-way audio	N/A	
<b>Decoding</b>		
Decoding format	H.265+/H.265/ H.264+/H.264	
Recording resolution	4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF	
Playback mode	Normal/Smart, Event, Tag, Eternal File	
Synchronous playback	4-ch	8-ch
Live view window division	1/4	1/4/6/8/9
Aux port window division	1/4	1/4/6/8/9
Capability	4-ch@1080p (25 fps), 4-ch@4 MP (12 fps)	
Stream type	Video, Video & Audio	
<b>Network</b>		
Remote connection	16	
Network protocol	TCP/IP, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, UPnP™	
Network interface	1, RJ-45 10/100 Mbps self-adaptive Ethernet interface	
<b>Wireless Parameter</b>		
Frequency band	2.4 GHz	
Antenna structure	2 × 2MIMO	
Transmission speed	144 Mbps	
Transmission standard	IEEE 802.11b/g/n	
<b>Auxiliary Interface</b>		
SATA	1 SATA interface	
Capacity	Up to 6 TB capacity for each disk	
Alarm in/out	N/A	
USB interface	Rear panel: 2 × USB 2.0	
<b>General</b>		
Power supply	12 VDC, 1.6 A	
Consumption (without HDD)	≤ 10 W	
Working temperature	-10 °C to 55 °C (14 °F to 131 °F)	
Working humidity	10% to 90%	
Chassis	Mini 1U	
Material	Metal box	


<b>Dimension (W × D × H)</b>	265 × 246 × 48 mm (10.4" × 9.7" × 1.9")
<b>Weight (without HDD)</b>	≤ 1.6 kg (3.5 lb)
<b>Certification</b>	
<b>FCC</b>	Part 15 Subpart B, ANSI C63.4-2014
<b>CE</b>	EN50130-4, EN 61000-3-2, EN 61000-3-3

## Dimension



Unit: mm

## Physical Interface



No.	Description	No.	Description
1	Dual Wi-Fi antenna	5	HDMI interface
2	Power supply	6	LAN network interface
3	AUDIO OUT	7	USB interface
4	VGA interface	8	Ground

## Available Model

DS-7104NI-K1/W/M(C), DS-7108NI-K1/W/M(C)

Distributed by



### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Australia**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahikvision.com

**Hikvision Canada**  
T +1-866-200-6690  
sales.canada@hikvision.com

**Hikvision Thailand**  
T +662-275-9949  
sales.thailand@hikvision.com

**Hikvision Europe**  
T +31-23-5542770  
sales.eu@hikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0050  
Latam.support@hikvision.com

**Hikvision Turkey**  
T +90 (216)521 7070- 7074  
sales.tr@hikvision.com

**Hikvision Malaysia**  
T +601-7652-2413  
sales.my@hikvision.com

**Hikvision UK & Ireland**  
T +01628-902140  
sales.uk@hikvision.com

**Hikvision South Africa**  
Tel: +27 (10) 0351172  
sale.africa@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-450  
info.fr@hikvision.com

**Hikvision Kazakhstan**  
T +7-727-9730667  
nikia.panfilov@hikvision.ru

**Hikvision Vietnam**  
T +84-974270888  
sales.vt@hikvision.com

**Hikvision UAE**  
T +971-4-4432090  
salesme@hikvision.com

**Hikvision Singapore**  
T +65-6684-4718  
sg@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Tashkent**  
T +99-87-1238-9438  
uzb@hikvision.ru

**Hikvision Hong Kong**  
T +852-2151-1761  
info.hk@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
saleru@hikvision.com

**Hikvision Korea**  
T +82-(0)31-731-8817  
sales.korea@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
info.pl@hikvision.com

**Hikvision Indonesia**  
T +62-21-2933759  
Sales.Indonesia@hikvision.com

**Hikvision Colombia**  
sales.colombia@hikvision.com

03041022000317