

AI PoE Switch


SF-SW8FE2GE2GE-2BT-120W

- Total 120W Power Supply
- 10 ports PoE
- 2 ports Uplink

Product Features


- AI Watchdog Function
- 6KV Lightning & 8KV ESD Protection
- Support bt 60W High Power
- Auto-Adaption 250m Transmission

Ports Description




- ① 100Mbps PoE Ports
- ② 1000Mbps PoE Ports
- ③ bt 60W Power Ports
- ④ 1000Mbps Uplink Ports

Dimension (mm)



Installation Diagram



Specifications

Model	SF-SW8FE2GE2GE-2BT-120W
Ports	PoE (1~8):10/100Mbps PoE ports (RJ45) PoE (9~10):10/100/1000Mbps PoE ports (RJ45),Support bt 60W High Power LAN (11~12):10/100/1000Mbps uplink ports (RJ45)
Transmission Rate	2000Mbps Full Duplex; 10 or 100 or 1000 Mbps Half Duplex
Transmission Distance	Port1~8:10/100Mbps 130meters; 10Mbps Auto-adaption 250meters Port9~10:10/100/1000Mbps 130meters
Performance Specification	Bandwidth:9.6Gbps
	Network Latency (10 to 1000Mbps):≤16μs (use the 64byte package size)
	MAC address table: 8K
	Packet Forwarding Rate: 7.1Mpps
Networking Standard	IEEE 802.3i 10BASE-T/IEEE 802.3u 100BASE-TX
	IEEE 802.3ab 1000BASE-T
	IEEE 802.3x Flow Control
	IEEE 802.3af/at/bt Power over Ethernet
Power Support	Power Input: AC 90~240V Total≤120W AI Watchdog: Port 1~10 Power Output: PoE1~8 Port:1/2(+52V),3/6(GND)≤30W PoE9~10 Port:1245(+53V),3678(GND) Compatible1/2(+52V),3/6(GND)≤60W
Protection Level	Lightning Protection:6KV ESD Protection:8KV
Physical Specifications	Size(L*W*H): 190mm*140mm*43mm, Weight: 1.0KG
Working Environment	Operating Temperature: -30°C~60°C
	Storage Temperature: -40°C~70°C
	Operating Humidity: 10%~90% Non-condensing
	Storage Humidity: 5%~90% Non-condensing
Certification	CE
	FCC
	RoHS 2.0
Warranty	Whole Device: 1 year
Package Content	AC Power Cable, User Manual