

# TTE GPRS Simple

## GPRS Communication Module

### Description

TTE GPRS Simple is a communication module used for connection between Teletek Electronics intruder alarm panels via serial connection. TTE GPRS Simple is used to send alarm messages to monitoring center or end-user.

### Functional Specifications

- SMS notifications for test, main and back-up power supply;
- 6 telephone numbers for events notification;
- Up to 12 SMS messages;
- Indication for the network status, the connection to the control panel, etc.;
- Internet remote programming and control through AJAX SP PRO/MobileTTE;
- Input for AC monitoring – 9-35 VAC;
- Suitable for home automation control.



### Technical Specifications

- Power supply 9-30VDC;
- SMD PPTC fuses;
- Power Consumption:
  - Current state – 50 mA;
  - Transmission state – up to 2 A;
- Input filtration time – 0.5 sec;
- Micro USB port for module configuration;
- Operating frequency – 850/900/1800/1900 MHz;
- SIM interface;
- SD card for voice messages;
- Antenna connector – SMA male;
- Installation with 4-wire serial connection to ECLIPSE panels;
- Reset jumper.

### Packing Information

- **Single packing box** - 1 units TTE GPRS Simple (PCB), dimensions 105 x 108 x 46 mm
- **Master box** - 90 units TTE GPRS Simple, dimensions 560 x 362 x 320 mm

### Compatible Product Range

- **Eclipse series** - alarm panels
- **SB-U** - small universal box

### Contact Information